

## For Residential and Commercial Applications

Job Name \_\_\_\_\_

Contractor \_\_\_\_\_

Job Location \_\_\_\_\_

Approval \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor's P.O. No. \_\_\_\_\_

Approval \_\_\_\_\_

Representative \_\_\_\_\_

# LEAD FREE\*

## Poly-Alloy CrimpRing™ & CinchClamp™ Couplings



WP15P  
PEX x PEX CrimpRing™ Coupling

Poly-Alloy CrimpRing™ & CinchClamp™ Couplings and Coupling Kits are used for making WaterPEX® repairs in the field, continuing a run as well as transitioning from polybutylene pipe to WaterPEX® tubing.

### Specifications

System shall be plumbed using Watts WaterPEX® cross-linked polyethylene pipe, and all joints shall be made using Watts brass CrimpRing™ and/or poly-alloy CrimpRing™ fittings using either the Watts copper CrimpRing™ or stainless steel CinchClamp™\*\* crimping methods as outlined in the Watts WaterPEX® Installation Guidelines.

### Installation Note

Brass Couplings must be installed in accordance with all Watts WaterPEX® installation procedures, including information provided in WaterPEX® installation manual and guidelines.

### Approvals



- Manufactured in accordance with American Society for Testing and Materials (ASTM) F-877 and F-2159
- Listed by the National Sanitation Foundation to NSF Standards 14 and 61 for use in potable water systems
- Listed by NSF to be in compliant to the Uniform Plumbing Code
- Labeled B137.5 which indicates that it is compliant to the CSA Standards B137.5
- Manufactured from Acudel® engineered thermoplastic resin.

\*The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight.

\*\*Note: Watts WaterPEX CinchClamp™ fittings should not be used with wrot copper PEX fittings.

### Warning!

If connections must be made in temperatures below 30°F, caution must be taken to allow the WaterPEX to form a proper seal against the barb. Apply the connection slowly to ensure the PEX material conforms to the barb.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

# WATTS®

## Dimensions – Weights

MODEL	INLET			OUTLET			PKG. WEIGHT	
	<i>in.</i>	<i>mm</i>	<i>type</i>	<i>in.</i>	<i>mm</i>	<i>type</i>	<i>lbs.</i>	<i>kgs.</i>
<b>PEX CrimpRing Couplings</b>								
WP15P-0808PB	½	15	Crimp Fitting	½	15	Crimp Fitting	1	0.4
WP15P-1208PB	¾	20	Crimp Fitting	½	15	Crimp Fitting	2	0.9
WP15P-1212PB	¾	20	Crimp Fitting	¾	20	Crimp Fitting	2	0.9
WP15P-1612PB	1	25	Crimp Fitting	¾	20	Crimp Fitting	3	1.4
WP15P-1616PB	1	25	Crimp Fitting	1	25	Crimp Fitting	3	1.4
WP15P-2020PB	1¼	32	Crimp Fitting	1¼	32	Crimp Fitting	3	1.4
WP15P-1620PB	1	25	Crimp Fitting	1¼	32	Crimp Fitting	3	1.4



A Watts Water Technologies Company



**ISO 9001-2008**  
CERTIFIED

**USA:** 815 Chestnut St., No. Andover, MA 01845-6098; [www.watts.com](http://www.watts.com)

**Canada:** 5435 North Service Rd., Burlington, ONT. L7L 5H7; [www.wattscanada.ca](http://www.wattscanada.ca)